



chêne de l'est®

French manufacturing of parquet

Nature at your feet...

Maintenance of the
Chêne de l'est parquets

31.01.2017

IMPORTANT: you will find here the generalities to be respected for the maintenance of your parquet. The generalities and the specific maintenance are updated on our web site. Only the latest version shall prevail . The informations was last updated on 31.01.2017. This version replaces and invalidates all previous versions.

To protect the beauty of your parquet, it's imperative to follow some advice and use cleaning products specifically adapted to the parquet that you chose. The maintenance must be carefully realized and regularity for a perfect perpetuity of the decoration and the protection.

After the installation :

It is recommended to spend a fine coat of maintenance oil, of varnished wood floor protector 17 or Metamat as the case may be. It will protect the original aspect of your parquet.

In every case, refer to boards below for the applications corresponding at the various finishing.

(The maintenance oil is available in 4 aspects: natural for clear or not coloured wood, white for parquets oiled in white (or light grey), black for parquets oiled in black and wood stain for exotic wood or parquets oiled in dark stains.)

During the first 10 days, the coat which has just been applied hardens. During this period, do not cover (protective canvases), not arrange carpet on the parquet.

Do not move heavy furniture. Not wet the parquet, dry-clean simply with a broom or a vacuum cleaner (do not use filled textile).

Watch to fix skates of felt or leather protection under the feet of furniture and seats.

To prevent scratches, place in the entrance a quality doormat which will retain dusts and bits of gravel. Do not leave water or other liquids stagnate on your parquet (isolate flowerpots).

Ban ammonia products or abrasive cleaners, etc., all the materials and products susceptible to look of the slippery and the shine, the skates of furniture and chairs in teflon which overlay with pebbles and quite other lining element. It is important to respect these protective measures.

***Concerning the finishes of the Antique oak nr 5, 8, 49, 60, 82:** the specificity of these finishes is the " candle touch " which is obtained after the application of a wax polish.

If this " candle touch " does not suit to you, you can shade it off either by polishing the parquet, what will give him amore satiny effect and a smoother touch, or by applying some hard oil, as recommends it the manufacturer Surgand, what amounts to a coat of universal maintenance oil. This hard oil or universal maintenance oil has no mechanical power, but will only allow to shade off this "candle touch " .

****Concerning the finishe of the Antique oak nr 95:** after the installation, the parquet must be polished with the application of wax dark brown or without wax.

Current cleaning :

Dry careful cleaning with a vacuum cleaner. Wipe with a damp mop (always thoroughly wrung and never dripping) never wash your parquet with a lot of water, or with clear water.

Use a natural soap for oiled parquets or a neutral cleaner. Eliminate spots with a damp sponge and a neutral cleaner (natural soap for oiled wood floors or varnished wood floor daily cleaner).

Regular maintenance :

For the oiled parquets, it's essential to apply a coat of maintenance oil for parquet using a hand spryer or with a rag as the casemay be. And that so often that it turns out necessary.

Always prefer spray method which allows to master the quantity. Always make a test beforehand to see if the result suits.

It is imperative to treat the parquet regularly with the maintenance oil in the places of strong requests (places of passage, tracks of chairs, etc.)

The parquet will have to dry between 2 and 4 o'clock before being put back in service.

It is imperative to treat the parquet regularly with oil, hard wax oil, or wax.

The regular application of maintenance oil, oil, hard wax oil, or wax is necessary to regenerate the protective coating and keep in the oiled parquet or polished its natural and warm aspect.

For the lackered parquets, use varnished wood floor protector 17 (or Metamat), it has a highly protective effect and protect the original aspect of your parquet.

This product contains no silicones, and it is no slippery.

Denial of responsibility: the information given in our specifications and technical sheets - that they are supplied verbally, written or by means of tries - is offered for ondication, but without guarantee, because the quality of the application and the conditions escape our control. For more information, please contact our Customer service. We can not accept any responsibility relative to the results of products following upon such a use, beyond the value of the goods delivered by ourselves. It does not affect your consumer's rights.

Before starting the maintenance, please refer to the page of the generalities

PLANCHER D'AUTREFOIS®

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
PA 2 - aspect bois brut PA 3 - brun cendré	Maintenance oil natural	Natural soap	Maintenance oil natural	Hard wax oil raw wood aspect
PA 10 - poussière d'argile PA 14 - plancher du boulanger	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect
PA 12 - blanc PA 83 - marengo PA 84 - ardoise	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil white
PA 8 - crème * PA 82 - sépia	Universal Maintenance Oil	Natural soap	Universal Maintenance Oil	Wax white or hard wax oil white, very wiped, can also be used to put white back in holes.
PA 17 - gris nuage	Maintenance oil natural	Natural soap	Maintenance oil natural	Hard wax oil dark grey
PA 18 - gris clair	Maintenance oil natural	Natural soap	Maintenance oil natural	Hard wax oil light grey
PA 43 - vieux gris PA 50 - gris moyen PA 66 - gris pastel Route 66 PA 86 - gris dune	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
PA 21 - cannelle	Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Hard wax oil walnut
PA 5 - doré antique *	Universal Maintenance Oil	Natural soap	Universal Maintenance Oil	Wax dark brown
PA 16 - pain d'épices PA 4 - marron fumé Route 4 PA 6 - Haussmannien	Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Natural oil
PA 80 - brou de noix PA 81 - noir pur PA 87 - château noir	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Hard wax oil black
PA 1 - chaume claire PA 11 - épi de blé PA 22 - chaume antique PA 45 - cendré PA 47 - terre d'ombre PA 85 - pourpre	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
PA 60 - brun antique *	Universal Maintenance Oil	Natural soap	Universal Maintenance Oil	Wax rustic
PA 68 - gris de brume	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198
PA 90 - cristal vieilli	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198
PA 95 - brun manoir ciré **	Polish with a white pad with wax dark brown or without wax	Natural soap	Universal Maintenance Oil or polishing	Wax dark brown
PA 801 - vieilli 801	Imperative : apply a thick coat of Oil 2180	Natural soap	Oil 2180 in spray method in fine coat	

* and ** See previous page

Attention : always apply **very fine coats**.

The oak antique collection is mechanically aged, and we bring a particular care to the cleaning of edges, but it can arrive that a splinter appears. We cannot be held responsible in case of wounds. **Important :** always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched

Before starting the maintenance, please refer to the page of the generalities

COLLECTION LOFT

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
LO 500 - LOFT - rouge LO 501 - LOFT - blanc LO 502 - LOFT - vert amande LO 503 - LOFT - gris anthracite	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil

EXTRÊME

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
PE 410 B - Extrême - brossé noir PE 414 - Extrême - vieilli noir	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Hard wax oil black
PE 412 B - Extrême - brossé blanc PE 413 - Extrême - vieilli blanc	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Natural oil in very fine coat

PLANCHER DES ÎLES

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
PI 702 - Sable chaud	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
PI 703 - Sable gris	Maintenance oil natural	Natural soap	Maintenance oil natural	Hard wax oil smoked oak n°301
PI 700 - Sable blanc	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
PI 704 - Sable noir	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Natural oil

GAMME WELLNESS

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
R 566 - gris volcan	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
R 567 - terre de Bruyère	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood very wiped

Attention : always apply **very fine coats**.

Important : always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched.

Before starting the maintenance, please refer to the page of the generalities

CHÈNE SCIÉ ET FRÈNE SCIÉ

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
SC 600 - Chêne scié huile naturelle SC 617 - Chêne scié gris acier SC 618 - Chêne scié gris métal SC 619 - Chêne scié atelier blanc	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
SC 613 - Chêne scié extrême noir	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Hard wax oil black
SC 601 - Chêne scié blanchi SC FR 601 - Frêne scié blanchi	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil white
SC 605 - Chêne scié poivre noir	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Natural oil
SC 611 - Chêne scié pain d'épices	Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Natural oil
SC 607 - Chêne scié gris océan	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198
SC 602 - Chêne scié gris ciment	Maintenance oil natural	Natural soap	Maintenance oil natural	Special hard wax oil n°5198
SC 608 - Chêne scié misty grey SC 606 - Chêne scié poivre blanc SC FR 606 - Frêne scié poivre blanc SC 610 - Chêne scié poussière d'argile	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°6356
SC 612 - Chêne scié poudre de chaux SC 615 - Chêne scié gris gravier SC 621 - Chêne scié aspect bois brut	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect very wiped
SC 609 - Chêne scié poivre gris	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
SC 614 - Chêne scié gris givré	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Natural oil
SC 616 - Chêne scié gris perle	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil pearl grey
SC 622 - Chêne scié cristal	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198
GI ISC 22 - Fleur de coton scié huilé	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect
SC 801 - Chêne scié 801	Imperative : apply a thick coat of Oil 2180	Natural soap	Oil 2180 in spray method in fine coat	

Attention : always apply **very fine coats**.

Important : always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched.

Before starting the maintenance, please refer to the page of the generalities

CHÊNE VIEUX DE FRANCE®

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
VDF 900 - huile naturelle VDF 901 - brossé huile naturelle	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Natural oil
VDF 911 - brossé verni mat VDF 912 - gris brossé verni mat	Varnished wood floor protector 17 or Metamat	Lisabril	Varnished wood floor protector 17 or Metamat	
VDF 903 - brossé huile grise VDF 902 - huile grise	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
VDF 913 - Terre de Lune	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil light grey
VDF 323 - cérusé blanc	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil white very wiped
VDF 904 - huile cire noire	Maintenance oil natural	Natural soap	Alternate maintenance oil black and maintenance oil natural	Hard wax oil black
VDF 905 - vieille école VDF 917 - brossé vieille école	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect

PRIVILÈGE CAFÉ

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
CA 400 - Privilège café - Espresso CA 402 - Privilège café - Mokaccino CA 405 - Privilège café - Moka cherry CA 407 - Privilège café - Café Veneziano	Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Hard wax oil walnut
CA 401 - Privilège café - Cappuccino	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
CA 403 - Privilège café - Café viennois CA 406 - Privilège café - Café latté	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil smoked oak n°301
CA 404 - Privilège café - Café crème	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil light grey

Attention : always apply **very fine coats**.

Important : always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched.

Before starting the maintenance, please refer to the page of the generalities

GAMME NATURE PARQUETS VERNIS, HUILÉS OU CIRÉS

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
Oiled parquets Col. 312 B - Gris galet brossé huilé Col. 319 B - Brun havane brossé huilé	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
Col. 324 P - Gris Vendôme Col. 353 B - Esprit récup	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
Lacquered, stain lacquered parquets (or stain mat lacquered)	Varnished wood floor protector 17 or Metamat	Lisabril	Varnished wood floor protector 17 or Metamat	
Col. 310 B - Teinte 5022 brossé huilé Col. 317 B - Brun chocolat brossé huilé Col. 318 B - Brun moka brossé huilé	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Natural oil
Col. 342 P - Pain d'épices Col. 342 B - Brossé pain d'épices	Maintenance oil natural	Natural soap	Alternate maintenance oil wood stain and maintenance oil natural	Natural oil
Col. 341 P - Poussière d'argile Col. 341 B - Brossé poussière d'argile Col. 3409 - Poncé huilé blanc 3409 GI IBR 6 - Brossé huilé blanc 3409 Col. 303 - Arktiss poncé huilé Col. 303 B - Arktiss brossé huilé	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°6356
Col. 321 - Aspect bois brut huilé GI IBR 2 - Voile de lin brossé huilé	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect
Col. 305 B - Blanc nordique brossé huilé Col. 400 B - No visible brossé huilé	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Hard wax oil raw wood aspect
Col. 302 - Bianchi huilé Col. 302 B - Bianchi brossé huilé	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil white
Col. 311 B - Teinté blanc brossé huilé	Because film-forming properties of these finishing, you can wait 3 months following the traffic before beginning the maintenance with Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Hard wax oil white
Col. 100 S - Structuré 100 S - Zèbre	Maintenance oil white	Natural soap white	Maintenance oil white	Natural oil
Col. 103 S - Structuré 103 S - Gris baltique	Maintenance oil white	Natural soap white	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198
Col. 104 S - Structuré 104 S - Cristal	Maintenance oil natural	Natural soap	Alternate maintenance oil white and maintenance oil natural	Special hard wax oil n°5198

Attention : always apply **very fine coats**.

Important : always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched.

Before starting the maintenance, please refer to the page of the generalities

VRAI VIEUX CHÊNE

Finishing	After the installation	Current cleaning	Regular maintenance	Important renovation
VC 800 - Vrai vieux chêne - huilé VC 802 - Vrai vieux chêne - structuré huilé	Maintenance oil natural	Natural soap	Maintenance oil natural	Natural oil
VC 801 - Vrai vieux chêne - oxydé verni	Varnished wood floor protector 17 or Metamat	Lisabril	Varnished wood floor protector 17 or Metamat	

Attention : always apply **very fine coats**.

Important : always refer to the data sheets of the manufacturer. All the cleaning products are listed in our price list with their description. We can supply you the colors for retouch or accessories to be matched.



chêne de l'est®

Handcrafted French hardwood flooring

Nature at your feet...

Manufacturer of solid finished plank flooring
parquets and engineered flooring ready to lay

Chêne de l'est
24, rue de la Fontaine
57910 HAMBACH/France
Mail: contact@chenedelest.com
Tél. +33 (0)3 87 98 03 42
Fax +33 (0)3 87 98 53 50

